





Recommended solder patse thickness is 0.10 mm
Recommended PCB Layout

TOP-LINK



- Notes:
1 Material, Housing: PA 4.6 (30% Glass Filled)
Color Black.
Contact: Brass
2 Mechanical demands:
Plating Plunger: 0.4um Au over 1.4um Ni
Plating Body: 0.1um Au over 1.4um Ni.

USED ON

-

LDC	-
DIST	-

update remark	
REVISION	
RECORD	
APVD	
DATE	2007/12/26

DIMENSIONS IN MM TOLERANCES UNLESS OTHER SPECIFIED			
0	= ±		
0.0	= ±0.15		
0.00	= ±0.10		
0.000	= ±		
ANGLE: ±1°			
SURF TEXTURE: 32/			
REMOVE BURRS, BREAK			
SHARP EDGES R0.05 MAX			
DO NOT SCALE PRINT			
MATL	1	HT TR	FIN
DWN		APVD	
Benny		Lansing	
CHK		REL	
Andy			
NAME	BATTERY POGO CONNECTOR 2 POSITIONS		
SCALE	1:1	A4	
ND	DWG	ND	C-100219
SHEET	1 OF 1	REV	C

100219-2
PART NUMBER

Top-Link
Electronics Ltd.