






THIS INFORMATION IS CONFIDENTIAL AND IS DISCLOSED TO YOU ON CONDITION THAT NO FURTHER DISCLOSURE IS MADE BY YOU TO OTHER THAN TOP-LINK PERSONNEL WITHOUT WRITTEN AUTHORIZATION FROM TOP-LINK LTD.



DWG NO.
C-100272



TOP-LINK

Recommended solder paste thickness is 0.10 mm

Recommended PCB Layout

- Notes:
- 1 Material, Housing: PA 4,6 (30% Glass Filled)
Color: Black.
 - 2 Mechanical demands:
Contact: Brass
Plating Plunger: 0.4µm Au over 1.4µm Ni
Plating Body: 0.1µm Au over 1.4µm Ni

LDC
-
DIST
-

NEW		2011/03/29
REVISION		
RECORD		
APVD		
DATE		

DIMENSIONS IN MM TOLERANCES UNLESS OTHER SPECIFIED			
0	= ±		
0.0	= ±0.15		
0.00	= ±0.10		
0.000	= ±		
ANGLE: ±1°			
SURF TEXTURE: 32/			
REMOVE BURRS, BREAK			
SHARP EDGES R0.05 MAX			
DO NOT SCALE PRINT			
MATL	1	HT TR	—
DWN		APVD	
Benny		Lansing	
CHK		REL	
Andy			
NAME	BATTERY	PGGD	CONNECTOR 2 POSITIONS
SCALE	1:1	A4	
DWG	NO.	C-100272	
PAGE	1	OF	1
SHEET	1	OF	1
REV	B		

100272-2
PART NUMBER

USED ON
-